



CPWplus P Bench Scales



Speed, Performance, Value - Perfect Balance

- **Six models with a wide range of capacities to choose from** Introducing models for smaller jobs only needing 6Kg (13Lb) or 15Kg (33Lb) capacity as well as a model that can handle 200Kg (440Lb.)
- **Improved visibility** Now with a larger backlit LCD display and a flexible remote indicator for better viewing of readings.
- **Three smart new features** An RS232 bi-directional interface for computer / printer connection is now included as standard. The new hold function and the addition of lb:oz as an extra weighing unit make the CPWplus more user-friendly.
- **Sturdy construction for tough environments** With tough mild steel base and stainless steel pan the CPWplus can handle messy applications.
- **Power choices** Use the AC adapter or switch to the internal rechargeable battery when portability is needed (both included.)
- **Simple operation and set up** Features color-coded keys, tare function, and selectable weighing units to make your job easier and faster.
- **Plus these standard features:** Simple set-up and operation, splash-proof keypad, backlit LCD, auto-calibration through the keypad, weigh-below hook, overload indicator, low battery indicator, auto power-off.



The CPWplus line of industrial scales offers an expanded selection of models with capacities to meet more applications than ever. Easy to use, the CPWplus combines reliability and durability for weighing tasks in material testing, shipping and receiving, office, industrial and agricultural applications. With an RS232 interface, a hold function, and a large display with a remote indicator the CPWplus line gives you a versatile scale for less money.



Technical Specifications

| Model | CPWplus 6P | CPWplus 15P | CPWplus 35P | CPWplus 75P | CPWplus 150P | CPWplus 200P |
|----------------------|------------------------|-------------|-------------|-------------|--------------|--------------|
| Maximum capacity | 13lb/6000g | 33lb/15kg | 75lb/35kg | 165lb/75kg | 330lb/150kg | 440lb/200kg |
| Readability | 0.005lb/2g | 0.01lb/5g | 0.02lb/10g | 0.05lb/20g | 0.1lb/50g | 0.1lb/50g |
| Tare range | Full | Full | Full | Full | Full | Full |
| Repeatability (S.D.) | 2g | 5g | 10g | 20g | 50g | 50g |
| Linearity (±) | 4g | 10g | 20g | 40g | 100g | 100g |
| Platform size | 11.8x11.8" / 300x300mm | | | | | |

General Specifications

| | |
|----------------------------|--|
| Typical stabilisation time | 2 Sec |
| Units of measurement | Kilogram (kg), Carat (ct), Pound (lb), Pound-Ounce (lb-oz) |
| Interface | RS-232 bi-directional Interface |
| Operating temperature | 0° - 40°C |
| Compensated temperature | 32°F - 104°F |
| Power supply | 6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter |
| Calibration | Automatic External with user selectable calibration mass |
| Display | LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together |
| Housing | Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform |
| Overall dimensions (wxdxh) | 11.8x11.8x2" / 300x300x50mm |

Key Accessories

- RS-232 Cable
- Adam Printer
- AdamDU - Data Collection Program
- USB to RS-232 Interface Cable
- Thermal Paper for Adam Printer (5 Pack)



Adam Equipment - offices worldwide

www.adamequipment.com